SPECIFICATIONS

41530 SS Drain 10" Square Top, 6" Deep Specification

Josam series 41530 fabricated stainless steel (type 304), 10" square top, 6" deep, with no-hub bottom outlet, anchor tabs and perforated SS grate (standard).

[213] 9 3/4 SQ [247] - [51] (-WF OPTION) В B 4 1 3/16 [30] 1/4 (OPTION -WF) [7] 2 WIDE FLANGE [50] 1 5/16 [34] 2 6 1/16 (OPTION -CF) [154] [52] CLAMP AND FLANGE FILTER BASKET (-FB OPTION) 2 3/8 PRIMER TAP [60] (-50 OPTION) (-DB OPTION) - PIPE SIZE Ø7 5/8 [193]

OPTIONS:

-WF	2" wide flange		-CF	Clamp and flange	Model	Pipe size
-FB	Filter basket		-NG	No grate	41532	2"
-SB	Sediment bucket		-HG	Perf. Half grate	41533	3"
-VP	Secured grate		-3Q	Perf. 3/4 grate	41534	4"
-50	1/2" primer tap		-MG	Mesh, anti-slip grate		1
-BW	Butt-weld outlet (spec. 10, 40, 80)		-LG	Ladder grate		
-т	Threaded outlet		-SG	Perimeter slot grate		
-PFO	Push-Fit outlet		-316	Type 316L material		
-DB	Dome bottom strainer					

Josam product specifications in U.S. customary units are approximate and provided for reference only. For precise measurements, please contact Josam Technical Support. Josam reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Josam products previously or subsequently sold.

Notes:



STANDARD GRATE FREE AREA = 20.2 IN²

MEETS ADA AND HEEL-PROOF REQS.

A WATTS Brand

T: (800) 365-6726 • Josam.com